



>> RP-NA2330

2-Bay Desktop Gigabit SATA NAS

The device allows 2 connected hard disk, which boosts the capacity for your data sharing and backup needs. It uses the high-speed SATA interface, providing users excellent data storage and sharing capability. The device also supports RAID 0, RAID 1 and Linear modes for various HDD backup configuration.

The FTP server allows users to backup and share files with FTP client software. The Web server provides an easy way to share files by web site. The embedded printer server brings you terrific convenience on sharing your printer. The NAS also supports DDNS, which allows you to designate an easy-memorized domain name to this device. It equips 2* USB 2.0 ports for your USB storage devices and USB printer. You may also back-up files from your USB storage devices conveniently by pressing the "Backup" button.

Feature

- Supports hard disk drive hot-plug and unplug
- Supports software RAID (LINEAR, RAID 0,1) via software configuration
- Built-in BT (Bit Torrent) compatible P2P software
- Web-based UI for easy configuration
- Supports UPnP, fixed IP & DHCP client
- Built-in FTP server for users to transfer files using FTP client
- Built-in iTunes server and UPnP AV server
- Built-in MySQL database and photo gallery
- Supports CIFS/SMB for Windows, MAC, Linux Network remote users easily retrieve files
- Provides HD formatting function for new HD or USB storage
- Provides Password security for Web management & HD access
- Supports 32 concurrently connected users (Samba & FTP)
- Built-in auto power recovery capability

Specification

Standards	• IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab standards
Support Protocol	• TCP/IP, HTTP, SMB, FTP, DHCP, UPnP
File System	• EXT3
Interface	• 1*100/1000Mbps RJ-45 Ethernet port • 2* USB 1.1/2.0 ports. • 1*USB backup button, 1* Power On/Off Switch Button • One Reset to Factory Default Setting Button
Ethernet Connection speed	• 10/100/1000 Mbps
USB Connection speed	• Max. 480 Mbps
Support Hard Diskette	• 2* removable 3.5" SATA HDD up to 2TB
Memory	• Flash: 8MB, SDRAM: 128MB
Diagnostic LEDs	• Power (Blue); Status (Amber, Red) • LAN (1000Mbps Link/Act Green; 10/100Mbps Link/Act, Amber); HDD I (Green); HDD II (Green) USB I (R/W, Green); USB II (R/W, Green), HDD Full (Red), Backup (Green)
System	• Compatible with Windows 95 /98 /98SE /ME /XP /2000 /NT4.0 /Vista /Linux /MAC OS
Power Adapter	• DC12V 5A
Environment	• Temperature Operating: 0°C ~ 40°C • Temperature Storing: -10°C ~ 65°C
Dimension	• 210 * 130 * 120 mm
Certifications	• FCC, CE

Ordering information

RP-NA2330 2-Bay Desktop Gigabit SATA NAS